

# SPLIT SYSTEMS 2026



## BREEZELESS+ COMPACT ROUNDFLOW CASSETTE



- 360° Air Flow Panel
- Refrigerant Leakage Detect
- Louvre Position Memory
- Fresh Air Inlet
- Remote Enable Port
- Temperature Compensation
- Anti-cold Air Function
- Low Ambient Cooling
- Emergency Use Function
- Built-in Drain Pump
- Wired Control
- Central Control Management
- Voice Control
- Smart Home
- WiFi

The Midea Breezeless+ Compact Roundflow Cassette is the perfect solution for commercial, office or retail spaces. Its 360° air outlet delivers even airflow, ensuring consistent cooling or heating across every corner of a room.

### HIGH ENERGY EFFICIENCY

Up to SEER 6.8(A++)/SCOP 4.1 (A+).

### BREEZELESS+ EFFECT

2468 hourglass-shaped micro holes turn the airflow into thousands of tiny particles of cool air, softening the airflow to eliminate the feeling of cold draughts.

### 360° AIRFLOW OUTLET

360° air outlet provides even airflow circulation to cool or heat every corner of a room and keep a constant temperature.

### I-ECO DASHBOARD

With high precision power detection technology, users can see the energy consumption data of the systems on their APP. View statistics for the day, week, month, and even the current year. Every kilowatt hour of the systems can be seen clearly.

### ADJUSTABLE VANE & LONG AIRFLOW

The adjustable vane can be set between 0° and 75°, delivering airflow up to 5.5 metres to reach even the far corners of the room.

### SELF-CLEANING OUTDOOR UNIT

At the end of each operation the outdoor unit fan will run in reverse, removing dust to improve efficiency and reduce wear and tear.

### TWIN, TRIPLE, QUAD COMBINATIONS

Outdoor unit sizes 24,36,48 HP can be installed with multiple indoor units for increased flexibility.

### SMARTHOME APP

Control the air conditioner easily via the SmartHome app on your smartphone. With just a simple swipe, you will be able to turn the air conditioner on/off and select the appropriate mode and temperature. Voice control available by Alexa & Google Assistant.

### LED FASCIA DISPLAY

Built-in display for easy trouble shooting and system information.

### SYSTEM COMPONENTS



Outdoor unit



Indoor unit



IR Controller RG10-B (included)



Wired Controller KJR-120M1 (included)

## BREEZELESS+ COMPACT ROUNDFLOW CASSETTE

INDOOR			MCA4U-09HRFNX(GA)	MCA4U-12HRFNX(GA)	MCA4U-18HRFNX(GA)
PANEL			T-MBQ4-03AWD	T-MBQ4-03AWD	T-MBQ4-03AWD
OUTDOOR			MOX230-09HFN8-Q(GA)	MOX230-12HFN8-Q(GA)	MOX330U-18HFN8-Q(GA)
Nominal Cooling Capacity (min-max)	kW		2.64 (0.36-3.40)	3.52 (0.85-4.16)	5.28 (2.90-5.59)
Nominal Heating Capacity (min-max)	kW		2.93 (0.45-3.61)	3.81 (0.47-4.34)	5.57 (2.37-6.10)
UK Total Cooling Capacity	kW		3.02	3.9	5.3
Seasonal Efficiency SEER/Class	W/W		6.2/A++	6.8/A++	6.5/A++
Seasonal Efficiency SCOP/Class	W/W		4/A+	4.1/A+	4.1/A+
Power supply (indoor power via outdoor)	V- Ph-Hz		220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Cooling Current (min-max)	A		3.6(1.1-5.5)	4.5(1.3-6.4)	6.9(3.2-9.0)
Heating Current (min-max)	A		4.2(1.2-5.6)	4.5(1.1-6.2)	6.8(3.1-8.6)
Max.Current	A		9	9	13.5
Recommended Fuse Size (Outdoor)	A		16	16	16
Interconnecting/Indoor Power Wiring	No.		4 Core 1mm <sup>2</sup>	4 Core 1mm <sup>2</sup>	4 Core 1mm <sup>2</sup>
Indoor air flow (High - Low)	m <sup>3</sup> /h		500/460/400	620/520/330	660/540/300
Indoor Sound Pressure Level (High-Low)	dB(A)		37.0/35.5/33.0/26.0	42/38.5/31.5/25.5	44/41/31.5/25
Indoor unit	Dimensions (WxDxH) (body)	mm	570x570x245	570x570x245	570x570x245
	Packing (WxDxH)(body)	mm	715x640x295	715x640x295	715x640x295
	Dimensions (WxDxH) (panel)	mm	620x620x50	620x620x50	620x620x50
	Packing (WxDxH)(panel)	mm	715x700x115	715x700x115	715x700x115
	Net/Gross Weight (body)	Kg	14.6/17.5	16.1/18.8	16.2/19
	Net/Gross Weight (panel)	Kg	2.7/4.3	2.7/4.3	2.7/4.3
Drainage water pipe dia.	mm		ODØ25mm	ODØ25	ODØ25
Outdoor air flow	m <sup>3</sup> /h		2200	2200	2100
Outdoor sound pressure level	dB(A)		53	55.5	53
Outdoor unit	Dimensions (WxDxH)	mm	765x303x555	765x303x555	805x330x554
	Packing (WxDxH)	mm	887x337x610	887x337x610	915x370x615
	Net/Gross Weight	Kg	24.6/27	26.6/29	32.5/35.2
Refrigerant	Type		R32	R32	R32
	GWP		675	675	675
	Charged quantity	Kg	0.65	0.72	1.15
	Charged to	m	5	5	5
	Additional Charge	g/m	12	12	12
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Ø6.35/Ø9.52(1/4"/3/8")	Ø6.35/Ø9.52(1/4"/3/8")	Ø6.35/Ø12.7(1/4"/1/2")
	Max. pipe length	m	25	25	30
	Max. height difference	m	10	10	20
Operating temperature	Indoor (Cooling/Heating)	°C	16-32/0-30	16-32/0-30	16-32/0-30
	Outdoor (Cooling/Heating)	°C	-15-50/-15-24	-15-50/-15-24	-15-50/-15-25

Nominal Conditions: Cooling; indoor 27°C DB, 19°C WB, outdoor 35°C DB, 24°C WB.  
Nominal Conditions: Heating; indoor 20°C DB, outdoor 7°C DB, 6°C WB.

UK Conditions: Summer: indoor 21°C DB, 15°C WB, outdoor 27°C DB.  
Sound Pressure is measured 1.5m below the air-outlet at Nominal Conditions.

**DATA IS SUBJECT TO CHANGE, SCAN THE QR CODE FOR MOST RECENT PRODUCT INFORMATION**